



Duct Carbon Dioxide Sensor A/CO2-D

Description

CO2 transmitters can be used in a broad range of applications including air quality monitoring in buildings. CO2 concentration levels in buildings are monitored to provide an indication of occupancy and to drive a ventilation control strategy. An effective DCV (Demand Controlled Ventilation) strategy will conserve energy and maintain indoor air quality.



Features

- Simple installation (mounting hardware included)
- Ideally suited for larger HVAC return air ducts
- Offers standard 0-10 volt output
- Patented absorption infrared/gas sensing engine provides high accuracy in a compact low-cost package
- Patented ABC Logic™ self-calibration system eliminates the need for manual calibration in most applications
- Lifetime calibration guarantee.

Technical Specification


Measurement Range:	0-2000 PPM factory calibrated
Duct Air Velocity:	0 to 450 meter/min
Temp Dependence:	0.2% of full scale per °C
Stability:	<2% of full scale over the life of the sensor (15 years typical)
Accuracy:	±40 ppm +3% of reading @ 22°C (72°F) when compared with a factory certified reference
Non-linearity:	<1% of full scale @ 22°C (72°F)
Pressure Dependence:	0.13% of reading per mm of mercury
Calibration:	Sensors will be calibrated at zero and span at the factory. Calibration in the field will not be required. Sensors will be shipped with ABC Logic™ turned on.
Response Time:	Three minutes typical for a 90% step change at low duct speeds
Sampling Rate:	Every two seconds, 25% duty cycle
Warm-up Time:	< two minutes (operational); 10 minutes to achieve maximum accuracy
Operating Conditions:	Temperature: 0...50°C Humidity: 0...95% RH, non-condensing
Storage Conditions:	-20°C...70°C
Output:	0...10 Vdc
Power Supply:	18...30 Vac, 50/60 Hz or 18...42 Vdc
Dimensions:	Probe Length: 10.46 cm Probe Diam: 3.14 cm Junction Box Depth: 4.06 cm Height: 7.62 cm

Note: The A/CO2-D offers patented ABC Logic™ software for self correction of drift to better than ±20 ppm per year. The system is virtually free of maintenance and typically has a lifetime of more than 10 years.

Order Code

A/CO2-D Duct Carbon Dioxide Sensor

Installation & Wiring



Wiring:

RED - 24V
BROWN - Vout
BLACK - Ground

1. Before installing sensor, note the direction of the airflow. Ensure all mounting holes are sealed tightly.
2. Drill/Cut one 1 1/2" hole / Punch/Drill one 1/8" hole.
3. Slide sensor into 1 1/2" hole and secure with screws.
4. Connect conduit and make necessary wire connections.
5. Install lid, ensure it snaps into place.

E.C. Products Limited - Head Office

EC House, Amberley Way, Hounslow
Middlesex, TW4 6BH, United Kingdom

Tel: +44 (0)20 8569 4100 Fax: +44 (0)20 8569 4111