

Miniature Circuit Breakers DZ47

Page 1 of 2

Description

A range of miniature circuit breakers suitable 230/400Vac, 50/60Hz rated circuits up to 63 amps. They provide protection against overload and short circuits in electrical circuits and equipment in household and commercial applications. They can also be used for non-frequent changeover of electrical circuits.

Features

- Protection against overload and short circuit
- Contact position indication
- DIN rail mounted







Technical Specification

No. of Poles: 1P, 2P or 3P Rated Voltage: 230/400Vac

Rated Current: 1, 2, 4, 6, 10, 12, 16, 20, 25,

32, 40, 50, 63 amps

Tripping Curve:B, C or DRated Short Circuit Capacity:6kARated Frequency:50/60HzEnergy Limiting Class:3

Energy Limiting Class: 3

Rated Impulse Voltage withstand: 6.2kV

Electro-Mechanical Endurance: 4000 cycles

Connection Terminal: Pillar Terminal with clamp
Connection Capacity: Rigid conductor up to 25mm²

Mounting: DIN rail

Circuit Details

1 Pole:



2 Pole:



3 Pole:

Order Codes

Curve B	Curve C	Curve D	
DZ47- 63/1PxB	DZ47- 63/1PxC	DZ47- 63/1PxD	Single pole Miniature Circuit Breaker x= current rating see above
-	DZ47- 63/2PxC	-	Two pole Miniature Circuit Breaker x= current rating see above
	DZ47- 63/3PxC	DZ47- 63/3PxD	Three pole Miniature Circuit Breaker x= current rating see above


EC House, Amberley Way, Hounslow Middlesex, TW4 6BH, United Kingdom





Miniature Circuit Breakers DZ47

Page 2 of 2


Curves








Dimensions





E.C. Products Limited - Head Office

EC House, Amberley Way, Hounslow Middlesex, TW4 6BH, United Kingdom

Tel: +44 (0)20 8569 4100 Fax: +44 (0)20 8569 4111